

clearsound & clearsound^{live}
window transducer speaker window transducer speaker

scanmagnetics.com



ClearSound - A sound solution for sound problems

Sound Leisure's ClearSound transducer is the new audio device on the block, well on the windows anyway. This type of audio transducer, whilst seeing a new lease of life, was in fact first introduced into the market in 1964.

Convert your windows, walls, ceilings, dining table, bar tops etc. into intimate, non intrusive, high quality sounding boards. These incredible ClearSound transducers transform any amplified audio output signal (No greater than 20 watts RMS recommended) into a manageable discrete sound source. Simply attach the device, as instructed, to almost any existing surface ie. Wooden panels, Glass windows, Perspex, Plaster board, sit back and listen to the amazing results.

No unsightly speaker cabinets or ceiling speaker grilles, no holes in walls or ceilings, truly invisible ClearSound.

ClearSound Live

Clearsound Live MKII is the 'plug & play' ClearSound Transducer. An integral 2-channel amplifier delivering 20 watts RMS per channel ensures that the quality sound can be transmitted direct from your ipod, Mp3 player or even a laptop computer, through the window, door or wall etc.

A second ClearSound Transducer can be linked to the ClearSound Live, a multiple setting switch allows the option of mono or stereo plus, gain control switches can increase- decrease the output level. A volume control is also a feature of the ClearSound Live MKII.

D. Multiple setting switch.

Switch settings alter the output of the ClearSound to a low gain boost/cut and stereo setting when used with an optional ClearSound slave unit.

	ON	OFF
SW1	MONO	STEREO
SW2	CH2 ON	CH2 OFF
SW3	GAIN	GAIN
SW4	GAIN	GAIN

SW3 and SW4 control the level of gain increase/ decrease the table below shows the effect these switches can have on the output (see notes)

SW3	SW4	GAIN (dB)
ON	ON	20
OFF	ON	26
ON	ON	32
OFF	ON	36


Signal IN. 3.5 Stereo Jack ●

Volume Control ●

Power Supply 18v DC ●

Speaker OUT. 1.3 Centre positive ●

Power Output. Connection to optional ClearSound Slave Speaker



Specifications

Power Handling	20 watts RMS per channel.
Freq. Response	20Hz-20Khz dependent on size and thickness of driven surface.
Impedence	8 Ohms.

Dimensions

ClearSound - 120mm x 46mm - Weight 1 Kg
ClearSound Live - 120mm x 75mm - Weight 1.5kg's

Fully sealed lexan plastic casing, waterproof and corrosion resistant.
Standard colour is black, however a wide range of colours are available on request.

